

RESIDENTIAL WEATHERIZATION Rebate Claim Form



FOR UPGRADES COMPLETED ON OR BEFORE 9/30/2026

Homeowner Name: Jane Doe	Street Address: 123 Main St
--------------------------	-----------------------------

Requirements Checklist		
All boxes must be checked:		
☒	1	Insulation installed in a Maine: (check one) ☒ single-family, OR ☐ duplex, OR ☐ condominium (number of units in building: _____), OR ☐ mobile home, OR ☐ mixed-use building with one or two housing units and no commercial electrical meter(s)
☒	2	Insulated space heated the entire heating season
☒	3	Rebate claim form emailed or postmarked within six months of project completion
☒	4	Upgrade completed by an Efficiency Maine Residential Registered Vendor
☒	5	Upgrade was not part of the construction of a new home or addition
☒	6	Weatherization Requirements Checklist attached

Check when applicable		
☐	7	W-9 attached if the home is owned by a business and the business is the rebate recipient (one-time requirement)

Additional Requirements for Low- and Moderate-Income Customers		
☒	1	Condominium or building is owner's principal residence
☐	2	Customer eligibility verified (check one): ☐ Low Income - Customer participates in MaineCare, TANF, SNAP, or HEAP ☒ Moderate Income - Customer has Adjusted Gross Income of up to \$70,000 for single filers or \$100,000 for joint filers <i>Note: If customer is not verified prior to claim submission, the claim may not qualify for a low- or moderate-income rebate, or it may be delayed</i>

Blower Door Test Results. Enter results or select reason not performed.			
Pre-Upgrade CFM50:	2689	Post-Upgrade CFM50:	1894
Reason not performed: ☐ Health and safety risk ☐ Wood or pellet stove in operation ☐ In-progress home repairs		Reason not performed: ☐ Health and safety risk ☐ Wood or pellet stove in operation ☐ In-progress home repairs	

RESIDENTIAL WEATHERIZATION Rebate Claim Form

FOR UPGRADES COMPLETED ON OR BEFORE 9/30/2026



Customer Information									
Homeowner Name:	Jane Doe								
Installation Address:	Address	123 Main St	Town	Anywhere	State	ME	Zip	04000	
Mailing Address:	Address	123 Main St	Town	Anywhere	State	ME	Zip	04000	
Homeowner Email Address:	jdoe@gmail.com								
Homeowner Phone Number:	207-812-3456								
Pre-upgrade Primary Heating Fuel:	☐ N/A (new construction) ☒ Oil ☐ Kerosene ☐ Propane ☐ Natural Gas ☐ Wood ☐ Heat Pump(s) ☐ Electric Baseboard ☐ Other								
Natural Gas Utility (if applicable):	☐ Bangor ☐ Maine ☐ Summit ☐ Unital								

Upgrade Details						
#	Upgrade Type	Location (attic, wall, basement, underbelly)	Square Feet Insulated	Pre-Upgrade R-Value	Post-Upgrade R-Value	Cost
1	Air Sealing	Not applicable	N/A	N/A	N/A	\$ 250.00
2	Insulation	Attic	960	18	60	\$ 3,600.00
3	Insulation	Basement	512	1	13	\$ 5,248.00
4	Insulation					\$
5	Health & Safety	When calculating rebate, health & safety cost is capped at 25% of total air sealing and insulation project cost.				\$ 525.00

Rebate Calculation		
1	Total Project Cost (add rows 1 - 5 in "Upgrade Details" section, above)	\$ 9,623.00
2	Rebate Percentage Low Income = 80% Moderate Income = 60% Any Income = 40%	60 %
3	Unadjusted Rebate Amount (multiply row 1 by row 2)	\$ 5,773.80
4	Lifetime Limit (per condominium or building)* Low Income lifetime limit = \$8,000 in insulation and air sealing rebates Moderate Income lifetime limit = \$6,000 in insulation and air sealing rebates Any Income lifetime limit = \$4,000 in insulation and air sealing rebates	\$ 6,000.00
5	Previous Insulation and Air Sealing Rebates Issued for This Building or Condominium	\$ 500.00
6	Remaining Balance of Lifetime Limit (row 4 minus row 5)	\$ 5,500.00
7	Requested Rebate Amount (enter row 3 or row 6, whichever is less)	\$ 5,500.00
8	Homeowner's Required Contribution Amount, After Rebate (row 1 minus row 7)	\$ 4,123.00

Project Completion Date:	07/01/2026		
Rebate Recipient:	☐ Homeowner ☒ Residential Registered Vendor Rebates for low-income customers are sent to the vendor		
Residential Registered Vendor Company Name (and branch, if applicable):	Weatherization, Etc.		
SIGNATURES. Please sign below to certify that all information on this claim form is correct, all work has been completed, and to commit to help Efficiency Maine conduct an inspection.			
Registered Vendor Signature:		Date:	07/01/2026
Homeowner Signature:		Date:	07/01/2026

Weatherization Requirements Checklist



Homeowner Name: Jane Doe	Street Address: 123 Main St
--------------------------	-----------------------------

Health and Safety Requirements (all rows must be checked)			
Yes	N/A	#	Requirement
☒	☒	1	Carbon monoxide detector observed in living space if a combustion appliance exists within the home or if there is an attached garage
☒	☐	2	Upon project completion, all open combustion appliance flues tested for spillage during worst-case house depressurization (all exhaust fans and furnace turned on, flue dampers and doors to rooms with no exhaust fans and/or supply registers closed) and reported to homeowner if flue gas spillage did not stop within: • 2 minutes if appliance is warm • 5 minutes if appliance is cold
☐	☒	3	Advised homeowner to investigate any potentially asbestos-containing materials observed
☒	☒	4	Knob and tube wiring was either (1) not observed in space insulated, (2) removed, (3) found to be inactive, or (4) not a health and safety risk (air sealing only-upgrades)
☒	☒	5	Any dryer, bathroom, or kitchen fans that are vented into the upgraded space have been directly vented outdoors
☒	☐	6	If exposed ground or water is observed outside of basement sump pump pit, then homeowner notified of risks before upgrade started
☐	☒	7	Mechanical ventilation recommended
☒	☐	8	Pre- and post-upgrade blower door tests conducted*
☒	☐	9	Customer notified of foam off-gassing occupancy restrictions
☒	☐	10	Code-approved fire protection added to foam insulation installed as part of rebated work scope
☒	☐	11	Flammable materials installed as part of upgrade separated from chimneys, flue pipes, and non-IC-rated recessed lights by non-flammable materials
☒	☐	12	At-risk pipes where work is performed are protected from freezing
☒	☒	13	Radon mitigation system present or radon test recommended

* Required unless BPI recommends against (mold, asbestos, vermiculite, etc.)

Attic Insulation Requirements (if attic insulation was part of upgrade, all rows must be checked)			
Yes	N/A	#	Requirement
☒	☐	1	Attic penetrations (chimney, wire, pipe, duct, vents, drywall gaps) that are a part of insulated area were sealed
☒	☒	2	Attic insulated using one or more of following applications: • Open attic insulated to at least R-49 with blown-in insulation • Enclosed cavities filled to capacity with dense-pack insulation • Minimum 5" closed-cell spray foam used to insulate all surfaces • Closed-cell spray foam applied to within 1.5" of full depth of cavities that were subsequently enclosed • Open-cell spray foam applied to full depth of cavities that were subsequently enclosed
☒	☐	3	Baffles secured over exterior walls to separate insulation from ventilated eaves
☒	☐	4	Accesses through thermal boundary are insulated and air leakage is limited
☒	☐	5	Attic access protected by dam when blown-in insulation is used

Homeowner Name: Jane Doe	Street Address: 123 Main St
--------------------------	-----------------------------

Wall Insulation Requirements (if wall insulation was part of upgrade, all rows must be checked)			
Yes	N/A	#	Requirement
☐		1	Walls insulated using one or more of following applications: - Wall cavities: - Filled to capacity with either dense-pack insulation or open-cell spray foam - Insulated with at least 2" of closed-cell spray foam or rigid insulation (sealed along perimeter and at seams) - Walls covered by: - Minimum 2" rigid insulation (applied over the studs, and sealed along perimeter and at seams)

Basement Insulation Requirements* (if basement insulation was part of upgrade, all rows must be checked)			
Yes	N/A	#	Requirement
☒	☐	1	Accessible penetrations (chimney, wire, pipe, duct, vents, flooring gaps) that are a part of insulated area were sealed
☒		2	One or more of following applications was used to insulate the: - Basement: - Foundation walls insulated from 2 feet below grade to underside of first floor (including sill and band joist) with minimum 2" rigid or closed-cell spray foam - Floor cavities insulated: - to capacity with dense-pack insulation, OR - with at least 2" of foam (open-cell, closed-cell, or rigid) - Mobile home underbelly: - Underbelly filled to capacity with blown-in fiberglass - Minimum 2" closed-cell spray foam applied to subfloor, ducts, and pipes - Minimum 2" rigid insulation fastened to floor joists and sealed along perimeter and at seams Mobile home skirting insulation not rebate-eligible.

* Applies to basements, crawlspaces, mobile home underbellies, or other unconditioned space directly below a conditioned living area

Residential Registered Vendor Signature		
Please certify that all information on this checklist is correct by signing below.		
Residential Registered Vendor:	Weatherization, Etc.	
Employee Name (please print):	Jake Etzetra	
Signature:		Date: 07/01/2026